

ZyXEL GS1900 Series V2.10(AAxx.0)C0

Release Note

Date: Sep 30, 2015

This document describes the features in the GS1900 series product for its 2.10(AAxx.0)C0 release.

Support Platforms:

ZyXEL GS1900-8
ZyXEL GS1900-8HP Rev. A1
ZyXEL GS1900-8HP Rev. B1
ZyXEL GS1900-10HP
ZyXEL GS1900-16
ZyXEL GS1900-24E
ZyXEL GS1900-24
ZyXEL GS1900-24HP
ZyXEL GS1900-48
ZyXEL GS1900-48HP

Version:

System Version: V2.10(AAxx.0) | 09/10/2015

BootBase Version: V2.00 | 07/08/2015

Read Me First:

GS1900-8HP Rev. B1 and GS1900-10HP only can support firmware V2.10(AAxx.0)C0 or above version

Enhanced Features:

1. [PoE] Add Power-up mode for PoE switch.

Bug Fix:

-
1. [MGMT] User cannot login switch when password include special characters. (eITS#150400495)
 2. [MGMT] Using the special characters in the system name, location, contact will show an invalid character warning. (eITS#150800661)
 3. [IGMP] Fix the switch may not send igmp-query.

Known Issue:

-
1. [WebUI] Login page's system name characters will over the border when system name is set to 64 characters.
 2. [Logging] If user tries to restore an illegal configuration (unofficial), login will always show authentication fail.
 3. [WebUI] System name display incorrect when using the special characters.
 4. [WebUI] Some pages cannot display correct when IE 8 enable "Compatibility View Settings".
[Workaround] Upgrade IE browser to the latest version or disable "Compatibility View Settings."

Limitation of Settings:

-
1. 802.1s instances : 16
 2. Guest VLAN : 1
 3. Static MAC entries : 64
 4. The BWM works well with UDP only.

Change History:

V2.10(AAxx.0)C0 – 2015/09/23
V2.00(AAxx.2)C0 – 2015/04/10
V2.00(AAxx.1)C0 – 2015/01/06
V2.00(AAxx.0)C0 – 2014/08/11
V1.00(AAxx.0)C0 – 2013/08/14